

# HDMI to HDMI & DVI Splitter



The HDMI to HDMI & DVI Splitter can repeat one HDMI signal to HDMI & DVI signal sets support up to 2 different HDMI & DVI display terminals. Based on Cleared Edge technology, it supports up to 3.4Gbps data rate per channel, compliant with the DVI1.0 & HDMI 1.4 specification. This Splitter supports integrates EDID.

- HDMI 1.4 specification compliant Support 2K/4K 30HZ, DVI Support 1080P extended resolution formats up to 3.4Gbps data rate
- HDMI/DVI input port, up to HDMI/DVI output ports
- Unlimited cascading for more output ports or signal repeating
- Power-saving modes by source-side disablement (using output enable) as well as sink-side detection (using Hot Plug Detect)
- Multiple display/TV support
- General / ESD protection up to 3 kV
- Cable distance: 5m (In or Out) /max.
- Operating temperature: 0°C ~ +70°C
- Power free ( w/ Power Jack – USB Power Cable or DC Adapter Option)
- Weight : 40g include cable. Dimension :46 \* 48 \*15 ( mm ) +15cm Cable.
- Remark: The EDID read of Host port -----

Output port connection				EDID display
Output1	Connection	Output2	No connection	Output 1
Output1	No connection	Output2	Connection	Output 2
Output1	Connection	Output2	Connection	Output 2