

AUM-100-FCL (Type-C to RS-232 Cable-DCE Mode w/LED*9)

Features:

- FTDI Chipset. The FT231X is a USB to serial UART interface with full modem control.
- Standard USB TO RS-232 Adapter. Power free / Bus powered. Easy to install , Plug & Play
- Fully compliant with USB Spec 3.X 2.0. Compliant USB Spec1.1.
- Driver support: Win-XP, WinXX, MAC OS.-X ,Linux, Android
- Connector: USB (Type C Male), RS-232 (DB9 Female)
- Data rate: Over 1000kbps. ESD Protection for RS-232 I/O' +-15KV
- RS-232 for DCE Mode- w/RS-232 Null Modem..
- With : Power / DCD / RXD / TXD / DTR / DSR / RTS / CTS / RI
Power -- LED Red indicate, other – Red / Green LED indicate.
Signal / TTL out 1 - LED appear Green (V-)
Signal / TTL out 0 - LED appear Red (V+)
- With 1.0 meter Type C cable
- When updating drivers, please refer to <http://www.ftdichip.com/FTDrivers.htm> ,
- RS-232 (DB-9 Female) with screws and nuts

Specification:

DB-9 Pin assignment

Pin1	: DCD	<==	IN
Pin2	: TXD	==>	OUT
Pin3	: RXD	<==	IN
Pin4	: DSR	<==	IN
Pin5	: GND		
Pin6	: DTR	==>	OUT
Pin7	: CTS	<==	IN
Pin8	: RTS	==>	OUT
Pin9	: RI	<==	IN

