

AUM-100-FA (USB to RS-232 Cable-DCE Mode)

Features:

- FTDI Chipset. The FT231X is a USB to serial UART interface with full modem control.
- Standard USB TO RS-232 Adapter. Power free / Bus powered. Easy to install , Plug & Play
- Fully compliant with USB Spec 3.X 2.0. Compliant USB Spec1.1.
- Driver support: Win-XP, WinXX, MAC OS.-X ,Linux, Android
- Connector: USB (USB 2.0 A Male), RS-232 (DB9 Female)
- Data rate: Over 1000kbps. ESD Protection for RS-232 I/O' +-15KV
- RS-232 for DCE Mode- w/RS-232 Null Modem.
- With : Power , TX and RX –
Power -- LED Red indicate, TX -- LED Green indicate, RX – LED Orange indicate.
- With 1.0 meter USB cable
- When updating drivers, please refer to <http://www.ftdichip.com/FTDrivers.htm> ,
- RS-232 (DB-9 Female) with screws and nuts

Specification:

DB-9 Pin assignment

| | | | |
|------|-------|-----|-----|
| Pin1 | : DCD | <== | IN |
| Pin2 | : TXD | ==> | OUT |
| Pin3 | : RXD | <== | IN |
| Pin4 | : DSR | <== | IN |
| Pin5 | : GND | | |
| Pin6 | : DTR | ==> | OUT |
| Pin7 | : CTS | <== | IN |
| Pin8 | : RTS | ==> | OUT |
| Pin9 | : RI | <== | IN |

