

AUM-100-FC (Type-C to RS-232 Cable-DCE Mode)

Features:

- FTDI Chipset. The FT231X is a USB to serial UART interface with full modem control.
- Standard USB TO RS-232 Adapter. Power free / Bus powered. Easy to install , Plug & Play
- Fully compliant with USB Spec 3.X 2.0. Compliant USB Spec1.1.
- Driver support: Win-XP, WinXX, MAC OS.-X ,Linux, Android
- **Connector: USB (Type C Male), RS232(DB9 Female)**
- Data rate: Over 1000kbps. ESD Protection for RS-232 I/O' +-15KV
- RS-232 for DCE Mode- w/RS-232 Null Modem..
- With : Power , TX and RX –
Power -- LED Red indicate, TX -- LED Green indicate, RX – LED Orange indicate.
- With **1.0 meter** Type-C cable
- When updating drivers, please refer to <http://www.ftdichip.com/FTDrivers.htm>,
- **RS-232 (DB-9 Female) with screws and nuts**

Specification:

DB-9 Pin assignment

Pin1	: DCD	<==	IN
Pin2	: TXD	==>	OUT
Pin3	: RXD	<==	IN
Pin4	: DSR	<==	IN
Pin5	: GND		
Pin6	: DTR	==>	OUT
Pin7	: CTS	<==	IN
Pin8	: RTS	==>	OUT
Pin9	: RI	<==	IN

