

# AUM-100-MC (Type-C to RS-232 Cable-DTE Mode)

## Features:

- FTDI Chipset. The FT231X is a USB to serial UART interface with full modem control.
- Standard USB TO RS-232 Adapter. Power free / Bus powered. Easy to install , Plug & Play
- Fully compliant with USB Spec 3.X 2.0. Compliant USB Spec1.1.
- Driver support: Win-XP, WinXX, MAC OS.-X ,Linux, Android
- **Connector: USB (Type C Male), RS232(DB9 Male)**
- Data rate: Over 1000kbps. ESD Protection for RS-232 I/O' +-15KV
- RS-232 for DTE Mode.
- With : Power , TX and RX –  
Power -- LED Red indicate, TX -- LED Green indicate, RX – LED Orange indicate.
- With **1.0 meter** Type-C cable
- When updating drivers, please refer to <http://www.ftdichip.com/FTDrivers.htm>,
- **RS-232 (DB-9 Male) with screws and nuts**

## Specification:

### DB-9 Pin assignment

Pin1	:	DCD	<==	IN
Pin2	:	RXD	<==	IN
Pin3	:	TXD	==>	OUT
Pin4	:	DTR	==>	OUT
Pin5	:			GND
Pin6	:	DSR	<==	IN
Pin7	:	RTS	==>	OUT
Pin8	:	CTS	<==	IN
Pin9	:	RI	<==	IN

