

# AUM-100-MCL (Type-C to RS-232 Cable-DTE Mode w/LED\*9)

## Features:

- FTDI Chipset. The FT231X is a USB to serial UART interface with full modem control.
- Standard USB TO RS-232 Adapter. Power free / Bus powered. Easy to install , Plug & Play
- Fully compliant with USB Spec 3.X 2.0. Compliant USB Spec1.1.
- Driver support: Win-XP, WinXX, MAC OS.-X ,Linux, Android
- **Connector: USB (Type C Male), RS232(DB9 Male)**
- Data rate: Over 1000kbps. ESD Protection for RS-232 I/O' +-15KV
- RS-232 for DTE Mode.
- **With : Power / DCD / RXD / TXD / DTR / DSR / RTS / CTS / RI**  
Power -- LED Red indicate, other – Red / Green LED indicate.  
Signal / TTL out 1 - LED appear Green (V-)  
Signal / TTL out 0 - LED appear Red (V+)
- With 1.0 meter Type-C cable
- When updating drivers, please refer to <http://www.ftdichip.com/FTDrivers.htm> ,
- **RS-232 (DB-9 Male) with screws and nuts**

## Specification:

### DB-9 Pin assignment

Pin1	:	DCD	<==	IN
Pin2	:	RXD	<==	IN
Pin3	:	TXD	==>	OUT
Pin4	:	DTR	==>	OUT
Pin5	:			GND
Pin6	:	DSR	<==	IN
Pin7	:	RTS	==>	OUT
Pin8	:	CTS	<==	IN
Pin9	:	RI	<==	IN

